



RAYAH MARITIME SERVICES GROUP (RMSG)

Issuance Date 20th November, 2017

Pages: (Total) 2

Subject: Guidelines for onboard sampling for the verification of the Sulphur content of the fuel oil used on board ships

Refer to: Ship Owners, Operators, all agents & Surveyors

The Marine Environment Protection Committee, at its 70th session, approved the guidelines for on-board sampling for the verification of the sulphur content of the fuel oil used on board ships.

The Marine Environment Protection Committee, at its 70th session, recognizing the need to establish an agreed method for sampling to enable effective control and enforcement of liquid fuel oil being used on board ships under the provisions of MARPOL Annex VI, approved guidelines for on-board sampling for the verification of the sulphur content of the fuel oil used on board ships.

Sampling location

The on-board representative sample or samples should be obtained from a designated sampling point or points as agreed by the Administration taking into account the criteria given in points 1 to 5 below.

In the absence of the sampling point or points referred above, the fuel sampling point to be used should fulfil all of the following conditions:

1. be easily and safely accessible;
2. take into account different fuel oil grades being used for the fuel oil combustion machinery item;
3. be downstream of the in-use fuel oil service tank;
4. be as close to the fuel oil combustion machinery as safely feasible taking into account the type of fuel oil, flow-rate, temperature, and pressure behind the selected sampling point;
5. the sampling point should be located in a position shielded from any heated surface or electrical equipment and the shielding device or construction should be sturdy enough to endure leaks, splashes or spray under design pressure of the fuel oil supply line so as to preclude impingement of fuel oil onto such surface or equipment;
6. be proposed by the ship's representative and accepted by the inspector; and
7. the sampling arrangement should be provided with suitable drainage to the drain tank or other safe location.

Fuel oil samples may be taken at more than one location in the fuel oil service system to determine whether there is a possible fuel cross-contamination in the absence of fully segregated fuel service systems, or in case of multiple service tank arrangements.

Sample handling

The fuel oil sample should be taken when a steady flow is established in the fuel oil circulating system. The sampling connection should be thoroughly flushed through with the fuel oil in use prior to drawing the sample. The sample or samples should be collected in a sampling container or containers and should be representative of the fuel oil being used.

The sample bottles should be sealed by the inspector with a unique means of identification installed in the presence of the ship's representative. The ship should be given the option of retaining a sample.

The label should include the following information:



RAYAH MARITIME SERVICES GROUP (RMSG)

1. sampling point location where the sample was drawn;
2. date and port of sampling;
3. name and IMO number of the ship;

4. details of seal identification; and
5. signatures and names of the inspector and the ship's representative.

Act now

Ship Owners/ Managers/ Operators should follow the above guidelines for the method for sampling to enable effective control and enforcement of liquid fuel oil being used on board their vessels. Relevant safety management and other procedures shall be updated to incorporate the revised guidelines.

Best regards

Rayah Maritime Services Group (RMSG)

Email : tech@rayahgroup.com
Tel : +963 43 317670 / 317671
Fax : +963 43 317672